





10.4" Fully Rugged Tablet

CT-RU104PA

Intel® ATOM™ E3827 Processor

Full IP65

MIL-STD-810G Drop, Shock and Vibration Resistance

Wide Expansion Design for Data Capture

GNSS, Wi-Fi, Bluetooth, and Optional 4G LTE

Capacitive Multi-Touch Supports Gloved Touch, Water Rejection and Palm Rejection

Long Life, Revision Controlled

Don't let its stylish design fool you, Contec's CT-RU104PA 10.4" tablet is ready to take on the harshest environments. This fully rugged tablet features IP65 protection from dust and liquids, MIL-STD-810G rated drop, shock, and vibration resistance, and a wide temperature range of 4 to 122 degrees Fahrenheit. Powered by the Intel® Atom™ E3827 processor and equipped with the latest communication technology, The CT-RU104PA offers the performance and durability you need for optimal productivity, anytime, anywhere.

Specifications

System CT-RU104PA

CPU Intel® ATOM™ Processor

E3827 (1.75 GHz)

System Memory 1x DDR3L SO-DIMM up to 4 GB

Ethernet Gigabit Ethernet (RJ45)

Security TPM 1.2

Storage 64G mSATA SSD

Optional: 128GB mSATA SSD

Expansion Slot N/A

Communication WiFi 802.11 a/b/g/n/ac,

Bluetooth V4.0 + EDR, GNSS,

4G LTE (optional)

OS Support Windows® 10 IoT Enterprise

Optional: Linux

Barcode Optional 1D/2D integrated

Scanner barcode scanner

Display and Touch

LCD Size / Type 10.4" TFT LCD

Panel Ratio 4:3

Max. Resolution 1024 x 768 (Pixels)

Max. Brightness 350 nits

Touch Screen PCAP Multi-Touch supports

gloved touch, water rejection,

palm rejection

Glass Type 2mm hard top Gorilla Glass

Rubber Bumper Optional (Not integrated)

Physical Properties

Rubber Bumper Optional (Not integrated)

Dimensions 275 x 204 x 27 (mm)

(WxDxH)

Net Weight 1.3 Kg (2.87 lbs) ₁

I/O Ports

USB 2.0 Type A x1 USB 3.0 Type A x1

RS232 (optional USB

2.0 Type A)

Audio headset Jack x1 (Headphone /

N/A

microphone combo)

Docking connector x1 (32-pin)

Micro SD slot x1
Micro SIM slot x1
Micro HDMI N/A
RF Pass-through N/A

RF Pass-through Connector for

WLAN/GNSS/WWAN

Power Requirements

AC adapter 65W, 100-240V AC,

50/60Hz

Battery 3800mAh standard battery

Optional" 4500mAh hot-swappable battery

Environment

Operating -20 to 50 °C

Temperature

Storage -30 to 70 °C

Temperature

Operating 95% (non-condensing)

Humidity (RH)

IP Rating Full IP65

Ruggedness MIL-STD-810G certified,

6-foot drop resistance 2

Regulatory Certifications

EMC & Safety FCC-B, CE, CB

1. Actual weight varies by configurations and optional accessories

2. Testing is conducted and product certified with rubber bumper on. Rubber bumper is an optional ítem for this model.

* Specification subject to change without notice. Updated 23-Jun-2020.



I/O Diagram



Accessories



Ordering Information

Part Number	Description
CT-RU104PA-W4100	10.4" rugged tablet w/Windows® 10 IoT, 128 GB SSD, 4GB RAM
CT-RU104PA-W4200	10.4" rugged tablet w/Windows® 10 IoT, 256 GB SSD, 4GB RAM
CT-RU104PA-W410L	10.4" rugged tablet w/Windows® 10 IoT, 128 GB SSD, 4GB RAM, 4G LTE
CT-RU104PA-W420L	10.4" rugged tablet w/Windows® 10 IoT, 256 GB SSD, 4GB RAM, 4G LTE
CT-RU104PA-X4XXX	Additional configuration options (Part numbers defined by option selection)

Accessory Part Numbers	
22942	Rubber Bumper
22943	Shoulder Strap with D Rings
22944	Top Carry Handle with D Rings
22945	Hand Strap with D Rings
22946	D Rings x4
22947	Desktop Docking USB 2.0 x 4/RJ45 x 1/VGA x 1
22948	1-Bay Battery Charger
22950	4200mAh External Battery with Hook

Buy Online: www.ContecAmericas.com

Contec Americas Inc. 3991 Sarno Rd. Melbourne, FL 32934

Toll Free: (888) 285-0172 Local: (321) 728-0172 Email: sales@us.contec.com Global Website: www.Contec.com

